


Galaxy / MX846-7

MyWall Collection / Architectural metal envelopes for facades



- Hot-dip galvanised structural steel sheet corrugated profile with high structural efficiency.
- Metal envelopes for facades in industrial and commercial buildings and sports facilities.
- Product CE marked according to EN 14782 and EN 1090.
- Usable width of 846 mm by overlapping and production lengths up to 8,000 mm.
- Extensive colour palette and wide range of highly durable coatings.




TECZONE

Galaxy / MX846-7

MyWall Collection

MANUFACTURING CHARACTERISTICS



Useful width	846 mm
Maximum manufacturing length	8,000 mm
Steel type	Standard S220GD
Thickness	0.6 / 0.7 mm
Coatings	Standard Galvanised Z275 Galvanizado y lacado con poliéster silicona 25 µm
	Special HD, HDS, HDX, PVDF

Steel sheet certifications

Steel used according to EN 10346 (galvanised) and EN 10169 (organic coatings).

Profile Certification MX846-7

CE marked according to EN 14782:2006 and EN 1090-1:2009+A1:2011.



TECHNICAL DATA OF THE PROFILE

THICKNESS (mm)	PROFILE WEIGHT (kg/m ²)
0.6	6.96
0.7	8.12

REACTION TO FIRE

The MX846-7 profile has the reaction to fire classification A1 according to EN 13501-1:2018 (Euroclasses).

Galaxy / MX846-7

MyWall Collection

MAXIMUM ALLOWABLE LOADS UNDER PRESSURE (daN/m²)

e (mm)	SUPPORTS	SPAN BETWEEN SUPPORTS (mm)							
		750	1000	1250	1500	1750	2000	2250	2500
0.6		837	470	301	209	153	116	82	60
		833	511	344	240	177	135	107	87
		1012	625	424	300	221	169	134	108
0.7		982	552	353	245	180	135	95	70
		1015	619	405	281	206	158	125	100
		1236	757	506	351	258	198	156	126

1 daN/m² ≈ 1 kp/m²

MAXIMUM ALLOWABLE SUCTION LOADS (daN/m²)

e (mm)	SUPPORTS	SPAN BETWEEN SUPPORTS (mm)							
		750	1000	1250	1500	1750	2000	2250	2500
0.6		-931	-533	-344	-240	-170	-115	-82	-60
		-837	-470	-301	-209	-153	-117	-93	-75
		-1047	-588	-376	-261	-192	-147	-116	-94
0.7		-1108	-632	-405	-281	-202	-137	-97	-71
		-982	-552	-353	-245	-180	-138	-109	-88
		-1228	-690	-441	-306	-225	-172	-136	-110

1 daN/m² ≈ 1 kp/m²

NOTES:

- The values given in the table are allowable loads (unfactored), to be compared with the sum of characteristic loads (also unfactored) for each project
- Tables calculated according to Eurocode 3, part 1.3. Maximum permissible deflection criterion: L/200, where L is the distance between supporting purlins.
- Tables valid only for pre-dimensioning. The final structural calculation must be carried out by the designer in accordance with the regulations applicable in each country.
- In the case of pressure loads, the calculation assumes a bearing width of 200 mm. For smaller support widths, the permissible load values may be significantly reduced.
- For alternative configurations or load cases, please contact our technical department. Kingspan | Teczone expressly disclaims any liability arising from the use of these tables.



Download the latest version by scanning the QR code or by clicking [here](#).

Teczone Española S.A.U. reserves the right to modify the contents of this document without any prior warning. Every effort has been made to ensure that the content of this publication is accurate, but Teczone Española S.A.U. and its affiliated companies are not responsible for errors or information that may be misleading. Suggestions regarding the final use or application of the products or work methods are merely informative and Teczone Española S.A.U. and its affiliates do not accept any responsibility in this regard.