


CLIP18 PROFILE & U-CHANNEL RANGE

DESCRIPTION



CLIP18



U-CHANNELS


High quality cold formed profiles, made of certified galvanized steel sheet.

SCOPE OF APPLICATION


- Perimeter profile for gypsum board suspended ceilings, with single or double structure.
- Perimeter profile for gypsum board wall lining systems.
- U-Channel range: gypsum board furniture and interior design systems.

PRODUCT RANGE

CLIP18



U-31/28



U-19


U-31/24

U-30/28

U-30/30

U-26/28

U-26/30



PROFILE	THK (mm)	DIMENSIONS			Units/pallet	CE	NF	AENOR
		a	b	c				
CLIP 18	0.55	20	28	17	400	●	●	●
U-19	0.55	19	20	15	792	●		
U-31/28	0.55	31	28	28	350	●		●
U-31/24	0.55	31	24	24	400	●		●
U-30/28	0.55	30	28	28	630	●		
U-30/30	0.55	30	30	30	630	●		
U-26/28	0.55	26	28	28	630	●		
U-26/30	0.55	26	30	30	630	●		

CLIP 18 Standard length: 3,000 mm.

U-Channel range Standard length: 2,400 / 3,000 mm.

Other gauges and lengths on demand.

CLIP18 PROFILE & U-CHANNEL RANGE

ADVANTAGES

- Clip 18 profile: Clip fixing system, either in wall lining or false ceilings, which simplifies the assembly.
- U-Channel range: Dimpled/ribbed surface to facilitate the screwing of the boards and web stiffeners that increase the profile resistance.
- Quality certified steel sheet rolled by the leading European steel company.

TECHNICAL FEATURES

- Steel grade DX51 D (according to EN 10346 standard).
- Standard galvanisation type Z140 (140 g/m²).
- Galvanisation type Z275 (275 g/m²) for NF certified CLIP18 profile.

FIRE REACTION AND ACOUSTICS

- Fire reaction: Euroclass A1 (non combustible).
- Acoustic and fire reaction of Kingspan systems have been accredited by laboratory testing.

MANUFACTURING STANDARDS

- All products have the CE marking according to EN 14195:2005.

Additionally, some of the products have the following voluntary certifications (see table):

- AENOR N mark according to instruction RP 35.12.
- NF mark by CSTB according to instruction NF411.

STORAGE CONDITIONS

- Store on flat and sheltered surfaces.
- Do not expose to rain or direct sunlight.



Download the latest version by scanning the QR code or by clicking [here](#)

Teczone Española S.A.U. reserves the right to modify the contents of this document without any prior warning. Every effort has been made to ensure that the content of this publication is accurate, but Teczone Española S.A.U. and its affiliated companies are not responsible for errors or information that may be misleading. Suggestions regarding the final use or application of the products or work methods are merely informative and Teczone Española S.A.U. and its affiliates do not accept any responsibility in this regard.