






FIRE RESISTANT SYSTEMS FOR PARTITION WALLS, GYPSUM BOARD CEILINGS AND LININGS

DRYWALL PARTITIONING





Valid for spacing between uprights: 600 mm or less.

Dimensions (mm)			STD plate assay ○		Fire plate assay ●	
a	b (Upright)	c (Total)	Building system	Fire resistance	Building system	Fire resistance
	12,5	48	TS/48/73/1X13STD/-/1X13STD	EI 30 (E-095027-010)	TS/48/73/1X13F/-/1X13F	EI 45 (E-107929-001)
		70	TS/70/95/1X13STD/-/1X13STD		TS/70/95/1X13F/-/1X13F	
		90	TS/90/115/1X13STD/-/1X13STD		TS/90/115/1X13F/-/1X13F	
		100	TS/100/125/1X13STD/-/1X13STD		TS/100/125/1X13F/-/1X13F	
		125	TS/125/150/1X13STD/-/1X13STD		TS/125/150/1X13F/-/1X13F	
		150	TS/150/175/1X13STD/-/1X13STD		TS/150/175/1X13F/-/1X13F	
	15	48	TS/48/78/1X15STD/-/1X15STD	EI 45 (E-095027-011)	TS/48/78/1X15F/-/1X15F	EI 90 (E-112928-001)
		70	TS/70/100/1X15STD/-/1X15STD		TS/70/100/1X15F/-/1X15F	
		90	TS/90/120/1X15STD/-/1X15STD		TS/90/120/1X15F/-/1X15F	
		100	TS/100/130/1X15STD/-/1X15STD		TS/100/130/1X15F/-/1X15F	
		125	TS/125/155/1X15STD/-/1X15STD		TS/125/155/1X15F/-/1X15F	
		150	TS/150/180/1X15STD/-/1X15STD		TS/150/180/1X15F/-/1X15F	
	12,5	48	TS/48/73/1X13STD/LM/1X13STD	EI 30 (E-095027-010)	TS/48/73/1X13F/LM/1X13F	EI 45 (E-107929-001)
		70	TS/70/95/1X13STD/LM/1X13STD		TS/70/95/1X13F/LM/1X13F	
		90	TS/90/115/1X13STD/LM/1X13STD		TS/90/115/1X13F/LM/1X13F	
		100	TS/100/125/1X13STD/LM/1X13STD		TS/100/125/1X13F/LM/1X13F	
		125	TS/125/150/1X13STD/LM/1X13STD		TS/125/150/1X13F/LM/1X13F	
		150	TS/150/175/1X13STD/LM/1X13STD		TS/150/175/1X13F/LM/1X13F	
	15	48	TS/48/78/1X15STD/LM/1X15STD	EI 45 (E-095027-011)	TS/48/78/1X15F/LM/1X15F	EI 90 (E-112928-001)
		70	TS/70/100/1X15STD/LM/1X15STD		TS/70/100/1X15F/LM/1X15F	
		90	TS/90/120/1X15STD/LM/1X15STD		TS/90/120/1X15F/LM/1X15F	
		100	TS/100/130/1X15STD/LM/1X15STD		TS/100/130/1X15F/LM/1X15F	
		125	TS/125/155/1X15STD/LM/1X15STD		TS/125/155/1X15F/LM/1X15F	
		150	TS/150/180/1X15STD/LM/1X15STD		TS/150/180/1X15F/LM/1X15F	

FIRE RESISTANT SYSTEMS FOR PARTITION WALLS, GYPSUM BOARD CEILINGS AND LININGS

	Dimensions (mm)			STD plate assay ○		Fire plate assay ●	
	a	b (Upright)	c (Total)	Building system	Fire resistance	Building system	Fire resistance
 	12,5	48	98	TS/48/98/2X13STD/-/2X13STD	EI 60 (E-095027-012)	TS/48/98/2X13F/-/2X13F	EI 120 (E-112928-002)
		70	120	TS/70/120/2X13STD/-/2X13STD		TS/70/120/2X13F/-/2X13F	
		90	140	TS/90/140/2X13STD/-/2X13STD		TS/90/140/2X13F/-/2X13F	
		100	150	TS/100/150/2X13STD/-/2X13STD		TS/100/150/2X13F/-/2X13F	
		125	175	TS/125/175/2X13STD/-/2X13STD		TS/125/175/2X13F/-/2X13F	
		150	200	TS/150/200/2X13STD/-/2X13STD		TS/150/200/2X13F/-/2X13F	
	15	48	108	TS/48/108/2X15STD/-/2X15STD	EI 90 (E-095027-013)	TS/48/108/2X15F/-/2X15F	EI 120 (E-111890-002)
		70	130	TS/70/130/2X15STD/-/2X15STD		TS/70/130/2X15F/-/2X15F	
		90	150	TS/90/150/2X15STD/-/2X15STD		TS/90/150/2X15F/-/2X15F	
		100	160	TS/100/160/2X15STD/-/2X15STD		TS/100/160/2X15F/-/2X15F	
		125	185	TS/125/185/2X15STD/-/2X15STD		TS/125/175/2X15F/-/2X15F	
		150	210	TS/150/210/2X15STD/-/2X15STD		TS/150/210/2X15F/-/2X15F	
 	12,5	48	98	TS/48/98/2X13STD/LM/2X13STD	EI 60 (E-095027-012)	TS/48/98/2X13F/LM/2X13F	EI 120 (E-112928-002)
		70	120	TS/70/120/2X13STD/LM/2X13STD		TS/70/120/2X13F/LM/2X13F	
		90	140	TS/90/140/2X13STD/LM/2X13STD		TS/90/140/2X13F/LM/2X13F	
		100	150	TS/100/150/2X13STD/LM/2X13STD		TS/100/150/2X13F/LM/2X13F	
		125	175	TS/125/175/2X13STD/LM/2X13STD		TS/125/175/2X13F/LM/2X13F	
		150	200	TS/150/200/2X13STD/LM/2X13STD		TS/150/200/2X13F/LM/2X13F	
	15	48	108	TS/48/108/2X15STD/LM/2X15STD	EI 90 (E-095027-013)	TS/48/108/2X15F/LM/2X15F	EI 120 (E-111890-002)
		70	130	TS/70/130/2X15STD/LM/2X15STD		TS/70/130/2X15F/LM/2X15F	
		90	150	TS/90/150/2X15STD/LM/2X15STD		TS/90/150/2X15F/LM/2X15F	
		100	160	TS/100/160/2X15STD/LM/2X15STD		TS/100/160/2X15F/LM/2X15F	
		125	185	TS/125/185/2X15STD/LM/2X15STD		TS/125/175/2X15F/LM/2X15F	
		150	210	TS/150/210/2X15STD/LM/2X15STD		TS/150/210/2X15F/LM/2X15F	
 	12,5	48	146	TM/48/146/2X13STD/LM/2X13STD	EI 60 (E-095027-014)	TM/48/146/2X13F/LM/2X13F	EI 120 (E-114265-001)
		70	190	TM/48/190/2X13STD/LM/2X13STD		TM/48/190/2X13F/LM/2X13F	
		90	230	TM/48/230/2X13STD/LM/2X13STD		TM/48/230/2X13F/LM/2X13F	
		100	250	TM/48/250/2X13STD/LM/2X13STD		TM/48/250/2X13F/LM/2X13F	
		125	300	TM/48/300/2X13STD/LM/2X13STD		TM/48/300/2X13F/LM/2X13F	
		150	350	TM/48/350/2X13STD/LM/2X13STD		TM/48/350/2X13F/LM/2X13F	
	15	48	156	TM/48/156/2X15STD/LM/2X15STD	EI 120 (E-095027-015)	TM/48/156/2X15F/LM/2X15F	EI 120 (E-114265-002)
		70	200	TM/48/200/2X15STD/LM/2X15STD		TM/48/200/2X15F/LM/2X15F	
		90	240	TM/48/240/2X15STD/LM/2X15STD		TM/48/240/2X15F/LM/2X15F	
		100	260	TM/48/260/2X15STD/LM/2X15STD		TM/48/260/2X15F/LM/2X15F	
		125	310	TM/48/310/2X15STD/LM/2X15STD		TM/48/310/2X15F/LM/2X15F	
		150	360	TM/48/360/2X15STD/LM/2X15STD		TM/48/360/2X15F/LM/2X15F	



FIRE RESISTANT SYSTEMS FOR PARTITION WALLS, GYPSUM BOARD CEILINGS AND LININGS

	Dimensions (mm)			STD plate assay ○		Fire plate assay ●	
	a	b (Upright)	c (Total)	Building system	Fire resistance	Building system	Fire resistance
	12,5	48	123	TS/48/123/3X13STD/-/3X13STD	EI 90 (E-095027-016)	TS/48/123/3X13F/-/3X13F	EI 180 (E-114264-001)
		70	145	TS/70/145/3X13STD/-/3X13STD		TS/70/145/3X13F/-/3X13F	
		90	165	TS/90/165/3X13STD/-/3X13STD		TS/90/165/3X13F/-/3X13F	
		100	175	TS/100/175/3X13STD/-/3X13STD		TS/100/175/3X13F/-/3X13F	
		125	200	TS/125/200/3X13STD/-/3X13STD		TS/125/200/3X13F/-/3X13F	
		150	225	TS/150/225/3X13STD/-/3X13STD		TS/150/225/3X13F/-/3X13F	
	15	48	138	TS/48/138/3X15STD/-/3X15STD	EI 120 (E-111890-001)	TS/48/138/3X15F/-/3X15F	EI 180 (E-114264-001)
		70	160	TS/70/160/3X15STD/-/3X15STD		TS/70/160/3X15F/-/3X15F	
		90	180	TS/90/180/3X15STD/-/3X15STD		TS/90/180/3X15F/-/3X15F	
		100	190	TS/100/190/3X15STD/-/3X15STD		TS/100/190/3X15F/-/3X15F	
		125	215	TS/125/215/3X15STD/-/3X15STD		TS/125/215/3X15F/-/3X15F	
		150	240	TS/150/240/3X15STD/-/3X15STD		TS/150/240/3X15F/-/3X15F	
	12,5	48	123	TS/48/123/3X13STD/LM/3X13STD	EI 90 (E-095027-016)	TS/48/123/3X13F/LM/3X13F	EI 180 (E-114264-001)
		70	145	TS/70/145/3X13STD/LM/3X13STD		TS/70/145/3X13F/LM/3X13F	
		90	165	TS/90/165/3X13STD/LM/3X13STD		TS/90/165/3X13F/LM/3X13F	
		100	175	TS/100/175/3X13STD/LM/3X13STD		TS/100/175/3X13F/LM/3X13F	
		125	200	TS/125/200/3X13STD/LM/3X13STD		TS/125/200/3X13F/LM/3X13F	
		150	225	TS/150/225/3X13STD/LM/3X13STD		TS/150/225/3X13F/LM/3X13F	
	15	48	138	TS/48/138/3X15STD/LM/3X15STD	EI 120 (E-111890-001)	TS/48/138/3X15F/LM/3X15F	EI 180 (E-114264-001)
		70	160	TS/70/160/3X15STD/LM/3X15STD		TS/70/160/3X15F/LM/3X15F	
		90	180	TS/90/180/3X15STD/LM/3X15STD		TS/90/180/3X15F/LM/3X15F	
		100	190	TS/100/190/3X15STD/LM/3X15STD		TS/100/190/3X15F/LM/3X15F	
		125	215	TS/125/215/3X15STD/LM/3X15STD		TS/125/215/3X15F/LM/3X15F	
		150	240	TS/150/240/3X15STD/LM/3X15STD		TS/150/240/3X15F/LM/3X15F	

FIRE RESISTANT SYSTEMS FOR PARTITION WALLS, GYPSUM BOARD CEILINGS AND LININGS

LININGS



Valid for spacing between uprights: 600 mm or less.

	Dimensions (mm)			STD plate assay ○		Fire plate assay ●	
	a	b (Upright)	c (Total)	Building system	Fire resistance	Building system	Fire resistance
	12,5	48	73	TR/48/73/2X13STD	EI 30 (E-109117)	-	-
		70	95	TR/70/95/2X13STD		-	
		90	115	TR/90/115/2X13STD		-	
		100	125	TR/100/125/2X13STD		-	
		125	150	TR/125/150/2X13STD		-	
		150	175	TR/150/175/2X13STD		-	
	15	48	93	-	-	TR/48/93/3X15F	EI 90 (E-114260-001)
		70	115	-		TR/70/115/3X15F	
		90	135	-		TR/90/135/3X15F	
		100	145	-		TR/100/145/3X15F	
		125	170	-		TR/125/170/3X15F	
		150	195	-		TR/150/195/3X15F	

FIRE RESISTANT SYSTEMS FOR PARTITION WALLS, GYPSUM BOARD CEILINGS AND LININGS

DROPPED CEILINGS

Valid for spacing between uprights:: 400 mm or 600 mm.

	Dimensions (mm)			STD plate assay ○		Fire plate assay ●	
	a	b (Edge profiles)	c (Total)	Building system	Fire resistance	Building system	Fire resistance
	15	50	65	FT STEC 47/60+F47+1x15STD	EI 15 (14_07473)	-	-
	15	50	80	FT STEC 47/60+F47+2x15STD	EI 30 (14_07997)	-	-
	15	50	95	-	-	FT STEC 47/60+F47+3x15F	EI 60 (46485-002)



Download the latest version by scanning the QR code or by clicking [here](#)

This document describes fire resistance characteristics of the tests developed and an extrapolation of results for other tested materials, which may vary according to possible changes in products and standards in force. These characteristics should not be transferred to other products and systems outside of those tested.

Kingspan expressly disclaims any liability arising from the misuse of these tables.

For further information on any aspect and technical characteristics please contact our Design Support Service on +34 947 48 37 00 or email teczone@teczone.es.

Teczone Española S.A.U. reserves the right to modify the contents of this document without any prior warning. Every effort has been made to ensure that the content of this publication is accurate, but Teczone Española S.A.U. and its affiliated companies are not responsible for errors or information that may be misleading. Suggestions regarding the final use or application of the products or work methods are merely informative and Teczone Española S.A.U. and its affiliates do not accept any responsibility in this regard.